



# CONO





performance

Arcluce Code **0883000A-840-21**  
 Ex Code **S6401-21 CEI**  
 Code EAN **8054378205927**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	117lm/W
<b>Luminaire:</b>	35W , 4100lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS-M
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



# CONO

performance

Arcluce Code **0883000A-840-21**  
Ex Code **S6401-21 CEI**  
Code EAN **8054378205927**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO

# CONO

performance

Arcluce Code **0883001A-840-21**  
 Ex Code **S6403-21 CEI**  
 Code EAN **8054378205965**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	103lm/W
<b>Luminaire:</b>	35W, 3600lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS-W
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



# CONO

performance

Arcluce Code **0883001A-840-21**  
Ex Code **S6403-21 CEI**  
Code EAN **8054378205965**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO

# CONO



performance

Arcluce Code **0883002A-840-21**  
 Ex Code **S6405-21 CEI**  
 Code EAN **8054378206009**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	104lm/W
<b>Luminaire:</b>	35W, 3650lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type I
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



# CONO

performance

Arcluce Code **0883002A-840-21**  
Ex Code **S6405-21 CEI**  
Code EAN **8054378206009**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 104lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO

# CONO

performance

Arcluce Code **0883003A-840-21**  
 Ex Code **S6407-21 CEI**  
 Code EAN **8054378206047**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	110lm/W
<b>Luminaire:</b>	35W, 3850lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type III
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



# CONO

performance

Arcluce Code **0883003A-840-21**  
Ex Code **S6407-21 CEI**  
Code EAN **8054378206047**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 110lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO





# CONO

comfort

Arcluce Code **0883008A-840-21**

Ex Code

Code EAN **8054378342745**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	79lm/W
<b>Luminaire:</b>	35W , 2750lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS-M
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




# CONO

comfort

Arcluce Code **0883008A-840-21**

Ex Code

Code EAN **8054378342745**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 79lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO



# CONO

comfort

Arcluce Code **0883009A-840-21**

Ex Code

Code EAN **8054378342868**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	109lm/W
<b>Luminaire:</b>	35W , 3800lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS-W
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




# CONO

comfort

Arcluce Code **0883009A-840-21**

Ex Code

Code EAN **8054378342868**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 109lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO



# CONO

comfort

Arcluce Code **0883010A-840-21**

Ex Code

Code EAN **8054378342981**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	89lm/W
<b>Luminaire:</b>	35W, 3100lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type I
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.9 kg
<b>Size:</b>	A: Ø 300mm B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




# CONO

comfort

Arcluce Code **0883010A-840-21**

Ex Code

Code EAN **8054378342981**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 89lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO



# CONO

comfort

Arcluce Code **0883011A-840-21**

Ex Code

Code EAN **8054378343100**



## Technical information

**Light source:** LED, 4000K, CRI>80

**Luminaire efficacy:** 97lm/W

**Luminaire:** 35W, 3400lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz

**Wiring:** ON/OFF

**Optics:** type III

**Color:** Aluminium - 21

**Weight:** 4.9 kg

**Size:** A: Ø 300mm  
B: 330mm

CE

IP66

IK08



0,07m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Installation on bracket (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




# CONO

comfort

Arcluce Code **0883011A-840-21**

Ex Code

Code EAN **8054378343100**



## Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design, also available in catenary version, that enhances historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 97lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Installation on bracket (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO