



Outdoor floodlights

DUEDIECI







LUMINAIRE

- · Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- · Silicone rubber gaskets.
- · AISI 316 stainless steel external screws.
- · Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
 Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-5.

INSTALLATION

- · Waterproof grommet for single cable entry.
- Die-cast aluminium base plate (EN 47100).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

STANDARD PR	ODUCT	AVAILABLE OPTIONS
Wiring	ON/OFF (A)	
CCT	3000K (-830)	4000K (-840)
Colour	1 6	21



Q Löwenbräukeller - München, Germany





Outdoor floodlights

DUEDIECI

DUEDIECI



STANDARD COLOUR



DIMENSIONS






Code	Optic	Lumina Watt	ire Lumen	CRI	сст	Class	Wiring	Power Supply	A mm	B mm	C mm
0684014A-830-16	narrow 11°	10W	750lm	80	3000K		ON/OFF	220-240V 50/60Hz	110	251	135
0684010A-830-16	medium 18°	21W	1900lm	80	3000K	(ON/OFF	220-240V 50/60Hz	110	251	135
0684011A-830-16	flood 36°	21W	1850lm	80	3000K		ON/OFF	220-240V 50/60Hz	110	251	135


The photo represents the family product range. You can see the correct image of each product (code) on the website.

ACCESSORIES





for 1 light fitting for Ø 102 mm pole.



1099467X-16	1,80
Code	Ka

Adjustable pole bracket for 2 light fittings for Ø 102 mm pole.






aluminium visor

















LED driver included.









V Löwenbräukeller - München, Germany