


GOTHIC110

two way

Arcluce Code **0865004A-840-16**

Ex Code

Code EAN **8054378333293**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	16lm/W
Luminaire:	20W , 325lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	9.5 kg
Size:	A: 110mm B: 800mm

CE

IP66

IK10



0,09m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC110

twoway

Arcluce Code **0865004A-840-16**

Ex Code

Code EAN **8054378333293**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 16lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC110


GOTHIC110

three-way

Arcluce Code **0865005A-840-16**

Ex Code

Code EAN **8054378333378**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	24lm/W
Luminaire:	20W , 475lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	three way
Color:	Grey - 16
Weight:	9 kg
Size:	A: 110mm B: 800mm

CE

IP66

IK10



0,09m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC110

three-way

Arcluce Code **0865005A-840-16**

Ex Code

Code EAN **8054378333378**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 24lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC110



GOTHIC110

radial

Arcluce Code **0865006A-840-16**

Ex Code

Code EAN **8054378333453**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 33lm/W

Luminaire: 20W , 650lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: radial

Color: Grey - 16

Weight: 8.5 kg

Size: A: 110mm
B: 800mm

CE

IP66

IK10



0,09m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC110

radial

Arcluce Code **0865006A-840-16**

Ex Code

Code EAN **8054378333453**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 33lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC110


GOTHIC180

two way

Arcluce Code **0869013A-840-16**

Ex Code

Code EAN **8054378334931**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	45lm/W
Luminaire:	19W , 850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	16.2 kg
Size:	A: 180mm B: 1000mm

CE

IP66

IK10



0,18m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC180

twoway

Arcluce Code **0869013A-840-16**

Ex Code

Code EAN **8054378334931**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 45lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180


GOTHIC180

twoway

Arcluce Code **0869014A-840-16**

Ex Code

Code EAN **8054378335013**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	45lm/W
Luminaire:	19W , 850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	15.7 kg
Size:	A: 180mm B: 710mm

CE

IP66

IK10



0,13m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

GOTHIC180

twoway

Arcluce Code **0869014A-840-16**

Ex Code

Code EAN **8054378335013**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 45lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180


GOTHIC180

threeway

Arcluce Code **0869015A-840-16**

Ex Code

Code EAN **8054378335099**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	43lm/W
Luminaire:	28W , 1200lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	three way
Color:	Grey - 16
Weight:	15.7 kg
Size:	A: 180mm B: 1000mm

CE

IP66

IK10



0,18m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC180

threeway

Arcluce Code **0869015A-840-16**

Ex Code

Code EAN **8054378335099**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 43lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180


GOTHIC180

threeway

Arcluce Code **0869016A-840-16**

Ex Code

Code EAN **8054378335174**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	43lm/W
Luminaire:	28W , 1200lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	three way
Color:	Grey - 16
Weight:	15.2 kg
Size:	A: 180mm B: 710mm

CE

IP66

IK10



0,13m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC180

threeway

Arcluce Code **0869016A-840-16**

Ex Code

Code EAN **8054378335174**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 43lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180



GOTHIC180

radial

Arcluce Code **0869017A-840-16**

Ex Code

Code EAN **8054378335259**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	49lm/W
Luminaire:	36W , 1750lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Grey - 16
Weight:	15.2 kg
Size:	A: 180mm B: 1000mm

CE

IP66

IK10



0,18m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



GOTHIC180

radial

Arcluce Code **0869017A-840-16**

Ex Code

Code EAN **8054378335259**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 49lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180



GOTHIC180

radial

Arcluce Code **0869018A-840-16**

Ex Code

Code EAN **8054378335334**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	49lm/W
Luminaire:	36W , 1750lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Grey - 16
Weight:	8.7 kg
Size:	A: 180mm B: 710mm

CE

IP66

IK10



0,13m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

GOTHIC180

radial

Arcluce Code **0869018A-840-16**

Ex Code

Code EAN **8054378335334**



Specifications

The bollard light for outdoor private and public lighting, featuring a unique design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 49lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. GOTHIC180