

KAMPUS


die-cast aluminium trim



Arcluce Code **0571003A-830-21**

Ex Code

Code EAN **8054378397523**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	36lm/W
Luminaire:	7W , 250lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	asymmetric lmax=40°
Color:	Aluminium - 21
Weight:	2.6 kg
Size:	A: 250mm B: 246mm C: 116mm

CE

IP65

IK07



Appliance

- Shatterproof body made of fiber glass reinforced engineering plastic.
- Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- UV rays stabilized polycarbonate screen. 850°C glow wire test resistant, V0 self-extinguishing or in 3mm tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double waterproof grommet for through wiring.
- Supplied with recessed installation box made of engineering plastic.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

KAMPUS

die-cast aluminium trim



Arcluce Code **0571003A-830-21**

Ex Code

Code EAN **8054378397523**



Specifications

Shatterproof body made of fiber glass reinforced engineering plastic. Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. UV rays stabilized polycarbonate screen. 850°C glow wire test resistant, V0 self-extinguishing or in 3mm tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 36lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double waterproof grommet for through wiring. Supplied with recessed installation box made of engineering plastic.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. KAMPUS

KAMPUS


stainless steel trim



Arcluce Code **0571004A-830-30**

Ex Code

Code EAN **8054378397622**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	36lm/W
Luminaire:	7W , 250lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	asymmetric lmax=40°
Color:	Stainless Steel - 30
Weight:	3.4 kg
Size:	A: 250mm B: 246mm C: 116mm

CE

IP65



Appliance

- Shatterproof body made of fiber glass reinforced engineering plastic.
- Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- UV rays stabilized polycarbonate screen. 850°C glow wire test resistant, V0 self-extinguishing or in 3mm tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Recessed installation.
- Double waterproof grommet for through wiring.
- Supplied with recessed installation box made of engineering plastic.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.



KAMPUS

stainless steel trim



Arcluce Code **0571004A-830-30**

Ex Code

Code EAN **8054378397622**



Specifications

Shatterproof body made of fiber glass reinforced engineering plastic. Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. UV rays stabilized polycarbonate screen. 850°C glow wire test resistant, V0 self-extinguishing or in 3mm tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 36lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double waterproof grommet for through wiring. Supplied with recessed installation box made of engineering plastic.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. KAMPUS