



KLOU-IK180

radial

Arcluce Code **0870001A-840-16**
 Ex Code **S7013-16 CEI**
 Code EAN **8054378092671**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	33lm/W
Luminaire:	12W , 400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Grey - 16
Weight:	6.6 kg
Size:	A: Ø 184mm B: 250mm

CE

IP66

IK10



0,05m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.



Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

radial

Arcluce Code **0870001A-840-16**
Ex Code **S7013-16 CEI**
Code EAN **8054378092671**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 33lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180


KLOU-IK180

oneway

Arcluce Code **0870002A-840-16**

Ex Code

Code EAN **8054378335419**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	50lm/W
Luminaire:	14W , 700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Grey - 16
Weight:	10.8 kg
Size:	A: Ø 184mm B: 1000mm

CE

IP66

IK10



0,20m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



KLOU-IK180

oneway

Arcluce Code **0870002A-840-16**

Ex Code

Code EAN **8054378335419**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 50lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180


KLOU-IK180

oneway

Arcluce Code **0870003A-840-16**

Ex Code

Code EAN **8054378335495**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	50lm/W
Luminaire:	14W , 700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Grey - 16
Weight:	7.7 kg
Size:	A: Ø 184mm B: 500mm

CE

IP66

IK10



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

oneway

Arcluce Code **0870003A-840-16**

Ex Code

Code EAN **8054378335495**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 50lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180


KLOU-IK180

two way

Arcluce Code **0870004A-840-16**

Ex Code

Code EAN **8054378335570**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	50lm/W
Luminaire:	14W , 700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	10.8 kg
Size:	A: Ø 184mm B: 1000mm

CE

IP66

IK10



0,20m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



KLOU-IK180

twoway

Arcluce Code **0870004A-840-16**

Ex Code

Code EAN **8054378335570**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 50lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180


KLOU-IK180

twoway

Arcluce Code **0870005A-840-16**

Ex Code

Code EAN **8054378335655**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	50lm/W
Luminaire:	14W , 700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	7.7 kg
Size:	A: Ø 184mm B: 500mm

CE

IP66

IK10



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

twoway

Arcluce Code **0870005A-840-16**

Ex Code

Code EAN **8054378335655**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 50lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180



KLOU-IK180

radial

Arcluce Code **0870006A-840-16**

Ex Code

Code EAN **8054378335730**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	54lm/W
Luminaire:	26W , 1400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Grey - 16
Weight:	10.4 kg
Size:	A: Ø 184mm B: 1000mm

CE

IP66

IK10



0,20m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



KLOU-IK180

radial

Arcluce Code **0870006A-840-16**

Ex Code

Code EAN **8054378335730**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 54lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180



KLOU-IK180

radial

Arcluce Code **0870007A-840-16**

Ex Code

Code EAN **8054378335815**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	54lm/W
Luminaire:	26W , 1400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Grey - 16
Weight:	7.3 kg
Size:	A: Ø 184mm B: 500mm

CE

IP66

IK10



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

radial

Arcluce Code **0870007A-840-16**

Ex Code

Code EAN **8054378335815**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 54lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180

KLOU-IK180

oneway

Arcluce Code **0870008A-840-16**
 Ex Code **S7015-16 CEI**
 Code EAN **8054378092701**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	40lm/W
Luminaire:	6W , 240lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Grey - 16
Weight:	6.9 kg
Size:	A: Ø 184mm B: 250mm

CE

IP66

IK10



0,05m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

oneway

Arcluce Code **0870008A-840-16**
Ex Code **S7015-16 CEI**
Code EAN **8054378092701**





Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 4000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 40lm/W
Luminaire in insulation class I.
DRIVER INCLUDED.
Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
Brand ARCLUCE mod. KLOU-IK180

KLOU-IK180

twoway

Arcluce Code **0870009A-840-16**
 Ex Code **S7017-16 CEI**
 Code EAN **8054378092756**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	40lm/W
Luminaire:	6W , 240lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	two way
Color:	Grey - 16
Weight:	6.9 kg
Size:	A: Ø 184mm B: 250mm

CE

IP66

IK10



0,05m²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

KLOU-IK180

twoway

Arcluce Code **0870009A-840-16**
Ex Code **S7017-16 CEI**
Code EAN **8054378092756**



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 40lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KLOU-IK180