


# KRION-IN

performance





Arcluce Code **0781018A-840-21**  
 Ex Code **O8091-21 CEI**  
 Code EAN **8054378202766**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	100lm/W
<b>Luminaire:</b>	15W , 1500lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	narrow 12°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	2.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 346mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781018A-840-21**  
Ex Code               **08091-21 CEI**  
Code EAN              **8054378202766**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance






Arcluce Code **0781019A-840-21**  
 Ex Code **O8094-21 CEI**  
 Code EAN **8054378202803**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	109lm/W
<b>Luminaire:</b>	28W , 3050lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	narrow 12°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.2 kg
<b>Size:</b>	A: 70mm B: 142mm C: 639mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781019A-840-21**  
Ex Code               **08094-21 CEI**  
Code EAN             **8054378202803**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 109lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance



Arcluce Code **0781020A-840-21**  
 Ex Code **O8097-21 CEI**  
 Code EAN **8054378202841**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	111lm/W
<b>Luminaire:</b>	56W , 6200lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	narrow 12°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	8.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 1225mm

CE

IP67

IK10

⊕

👣

KG  
1000

🌡️ ↓

## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781020A-840-21**  
Ex Code               **08097-21 CEI**  
Code EAN              **8054378202841**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 111lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance







Arcluce Code      **0781021A-840-21**  
 Ex Code            **O8101-21 CEI**  
 Code EAN          **8054378202889**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	100lm/W
<b>Luminaire:</b>	15W , 1500lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	flood 26°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	2.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 346mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781021A-840-21**  
Ex Code               **08101-21 CEI**  
Code EAN              **8054378202889**

---



## Specifications

Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN




# KRION-IN

performance



Arcluce Code **0781022A-840-21**  
 Ex Code **O8104-21 CEI**  
 Code EAN **8054378202926**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	109lm/W
<b>Luminaire:</b>	28W , 3050lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	flood 26°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.2 kg
<b>Size:</b>	A: 70mm B: 142mm C: 639mm

CE

IP67

IK10



KG  
1000



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781022A-840-21**  
Ex Code               **08104-21 CEI**  
Code EAN              **8054378202926**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 109lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance



Arcluce Code **0781023A-840-21**  
 Ex Code **O8107-21 CEI**  
 Code EAN **8054378202964**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	111lm/W
<b>Luminaire:</b>	56W , 6200lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	flood 26°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	8.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 1225mm

CE

IP67

IK10



KG  
1000



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.


# KRION-IN

performance



Arcluce Code           **0781023A-840-21**  
Ex Code               **08107-21 CEI**  
Code EAN              **8054378202964**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 111lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance







Arcluce Code **0781024A-840-21**  
 Ex Code **O8111-21 CEI**  
 Code EAN **8054378203008**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	90lm/W
<b>Luminaire:</b>	15W , 1350lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wide flood 47°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	2.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 346mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781024A-840-21**  
Ex Code               **08111-21 CEI**  
Code EAN             **8054378203008**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 90lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance





Arcluce Code **0781025A-840-21**  
 Ex Code **O8114-21 CEI**  
 Code EAN **8054378203046**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	96lm/W
<b>Luminaire:</b>	28W , 2700lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wide flood 47°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.2 kg
<b>Size:</b>	A: 70mm B: 142mm C: 639mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781025A-840-21**  
Ex Code               **08114-21 CEI**  
Code EAN              **8054378203046**

---



## Specifications

Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 96lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN




# KRION-IN

performance



Arcluce Code **0781026A-840-21**  
 Ex Code **O8117-21 CEI**  
 Code EAN **8054378203084**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	98lm/W
<b>Luminaire:</b>	56W , 5500lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wide flood 47°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	8.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 1225mm

CE

IP67

IK10



KG  
1000



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781026A-840-21**  
Ex Code               **08117-21 CEI**  
Code EAN             **8054378203084**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 98lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance



Arcluce Code **0781027A-840-21**  
 Ex Code **O8121-21 CEI**  
 Code EAN **8054378203121**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	93lm/W
<b>Luminaire:</b>	15W , 1400lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	elliptic 10°x55°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	2.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 346mm

CE

IP67

IK10



KG  
1000



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781027A-840-21**  
Ex Code               **08121-21 CEI**  
Code EAN              **8054378203121**



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 93lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance



Arcluce Code **0781028A-840-21**  
 Ex Code **O8124-21 CEI**  
 Code EAN **8054378203169**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	100lm/W
<b>Luminaire:</b>	28W , 2800lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	elliptic 10°x55°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.2 kg
<b>Size:</b>	A: 70mm B: 142mm C: 639mm

CE

IP67

IK10



KG  
1000



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781028A-840-21**  
Ex Code               **08124-21 CEI**  
Code EAN              **8054378203169**

---



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance



Arcluce Code **0781029A-840-21**  
 Ex Code **08127-21 CEI**  
 Code EAN **8054378203206**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	102lm/W
<b>Luminaire:</b>	56W , 5700lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	elliptic 10°x55°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	8.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 1225mm

CE

IP67



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781029A-840-21**  
Ex Code               **08127-21 CEI**  
Code EAN              **8054378203206**

---



## Specifications

Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 102lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN




# KRION-IN

performance





Arcluce Code **0781030A-840-21**  
 Ex Code **O8131-21 CEI**  
 Code EAN **8054378203244**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	97lm/W
<b>Luminaire:</b>	15W , 1450lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wall washer lmax=18°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	2.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 346mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781030A-840-21**  
Ex Code               **08131-21 CEI**  
Code EAN              **8054378203244**



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 97lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance





Arcluce Code **0781031A-840-21**  
 Ex Code **O8134-21 CEI**  
 Code EAN **8054378203282**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	105lm/W
<b>Luminaire:</b>	28W , 2950lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wall washer lmax=18°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.2 kg
<b>Size:</b>	A: 70mm B: 142mm C: 639mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781031A-840-21**  
Ex Code               **08134-21 CEI**  
Code EAN              **8054378203282**



## Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 105lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN

# KRION-IN

performance




Arcluce Code **0781032A-840-21**  
 Ex Code **O8137-21 CEI**  
 Code EAN **8054378203329**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	106lm/W
<b>Luminaire:</b>	56W , 5950lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	wall washer lmax=18°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	8.4 kg
<b>Size:</b>	A: 70mm B: 142mm C: 1225mm



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 1000Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Recessed installation.
- Double grommet M20 for through wiring.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- END CAPS TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.

# KRION-IN

performance



Arcluce Code           **0781032A-840-21**  
Ex Code               **08137-21 CEI**  
Code EAN              **8054378203329**



## Specifications

Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. 1000Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-13. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 106lm/W Luminaire in insulation class I. DRIVER INCLUDED. Recessed installation. Double grommet M20 for through wiring. Steel spring clips. Supplied with extruded aluminium recessed box. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION-IN