


# KUBIX180

two way

Arcluce Code **0866013A-840-16**

Ex Code

Code EAN **8054378333538**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	37lm/W
<b>Luminaire:</b>	19W , 700lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	two way
<b>Color:</b>	Grey - 16
<b>Weight:</b>	8.2 kg
<b>Size:</b>	A: 180mm B: 1000mm

CE

IP66

IK10



0,18m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



# KUBIX180

two-way

Arcluce Code **0866013A-840-16**

Ex Code

Code EAN **8054378333538**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 37lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180


# KUBIX180

twoway

Arcluce Code **0866014A-840-16**

Ex Code

Code EAN **8054378333613**



## Technical information

**Light source:** LED, 4000K, CRI>80

**Luminaire efficacy:** 39lm/W

**Luminaire:** 18W , 700lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz

**Wiring:** ON/OFF

**Optics:** two way

**Color:** Grey - 16

**Weight:** 13.7 kg

**Size:** A: 180mm  
B: 500mm

CE

IP66

IK10

0,09m<sup>2</sup>

0,09m<sup>2</sup>

## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

# KUBIX180

two-way

Arcluce Code **0866014A-840-16**

Ex Code

Code EAN **8054378333613**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 39lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180


# KUBIX180

threeway

Arcluce Code **0866015A-840-16**

Ex Code

Code EAN **8054378333699**



## Technical information

**Light source:** LED, 4000K, CRI>80

**Luminaire efficacy:** 39lm/W

**Luminaire:** 28W , 1100lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz

**Wiring:** ON/OFF

**Optics:** three way

**Color:** Grey - 16

**Weight:** 8.3 kg

**Size:** A: 180mm  
B: 1000mm

CE

IP66

IK10



0,18m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



# KUBIX180

threeway

Arcluce Code **0866015A-840-16**

Ex Code

Code EAN **8054378333699**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 39lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180


# KUBIX180

three way

Arcluce Code **0866016A-840-16**

Ex Code

Code EAN **8054378333774**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	39lm/W
<b>Luminaire:</b>	28W , 1100lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	three way
<b>Color:</b>	Grey - 16
<b>Weight:</b>	13.8 kg
<b>Size:</b>	A: 180mm B: 500mm

CE

IP66

IK10



0,09m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

# KUBIX180

threeway

Arcluce Code **0866016A-840-16**

Ex Code

Code EAN **8054378333774**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 39lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180





# KUBIX180

radial

Arcluce Code **0866017A-840-16**

Ex Code

Code EAN **8054378333859**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	46lm/W
<b>Luminaire:</b>	36W , 1650lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	radial
<b>Color:</b>	Grey - 16
<b>Weight:</b>	13 kg
<b>Size:</b>	A: 180mm B: 1000mm

CE

IP66

IK10



0,18m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



# KUBIX180

radial

Arcluce Code **0866017A-840-16**

Ex Code

Code EAN **8054378333859**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 46lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180



# KUBIX180

radial

Arcluce Code **0866018A-840-16**

Ex Code

Code EAN **8054378333934**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	46lm/W
<b>Luminaire:</b>	36W , 1650lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	radial
<b>Color:</b>	Grey - 16
<b>Weight:</b>	12.5 kg
<b>Size:</b>	A: 180mm B: 500mm

CE

IP66

IK10



0,09m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs.
- Supplied with power cable.

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

# KUBIX180

radial

Arcluce Code **0866018A-840-16**

Ex Code

Code EAN **8054378333934**



## Specifications

The geometric design bollard light for outdoor lighting  
Extruded aluminium body. Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 46lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. KUBIX180