


PIXOL200

performance



Arcluce Code **0256000A-830-21**

Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	116lm/W
Luminaire:	38W , 4400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	spot 10°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code **0256000A-830-21**

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 116lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. PIXOL200


PIXOL200

performance



Arcluce Code **0256001A-830-21**

Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	38W , 3900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 37°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm

CE

IP66



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code **0256001A-830-21**

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. PIXOL200


PIXOL200

performance



Arcluce Code **0256003A-830-21**

Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	113lm/W
Luminaire:	38W , 4300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	very wide flood 70°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code **0256003A-830-21**

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 113lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. PIXOL200

PIXOL200

performance




Arcluce Code **0256010A-830-21**
Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	116lm/W
Luminaire:	69W , 8000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 15°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code **0256010A-830-21**

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 116lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. PIXOL200

PIXOL200

performance



Arcluce Code **0256011A-830-21**
Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	104lm/W
Luminaire:	69W , 7150lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 40°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm

CE

IP66



IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code **0256011A-830-21**

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 104lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. PIXOL200


PIXOL200

performance



Arcluce Code **0256013A-830-21**

Ex Code



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	116lm/W
Luminaire:	69W , 8000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	very wide flood 70°
Color:	Aluminium - 21
Weight:	5.2 kg
Size:	A: 200mm B: 200mm C: 150mm



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Waterproof grommet for single cable entry.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

PIXOL200

performance



Arcluce Code

0256013A-830-21

Ex Code



Specifications

PIXOL200 is the ceiling-mounted luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of engineering plastic metalized in high-vacuum or PMMA lenses. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 116lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Waterproof grommet for single cable entry.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. PIXOL200