

Recessed floor fittings

QUAD200




LUMINAIRE

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- AISI 316L stainless steel edge for flush with ground versions.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 10mm thermal-shock resistant tempered glass.
- 1000-1500Kg static load capacity.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-13.

INSTALLATION

- Recessed installation.
- Supplied with galvanized and painted steel recessed installation box.
- Supplied with power cable (0.7m).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

STANDARD PRODUCT		AVAILABLE OPTIONS
Wiring	ON/OFF (A)	
CCT	4000K (-840), RGBW	3000 (-830)
Colour	 30	




Photorealistic rendering.

Recessed floor fittings

QUAD200

FLUSH TRIM - RECESSED L BOX


Supplied with recessed installation box (1099034X).













STANDARD COLOUR

 30

DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0765008A-840-30	 spot 9°	37W	4050lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	171	340
0765007A-840-30	 medium 25°	37W	3800lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	171	340
0765022A-840-30	 wide flood 47°	37W	3500lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	171	340
0765012A-840-30	 elliptic 9°x52°	37W	3700lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	171	340
0765047A-840-30	 wall washer I _{max} =19°	37W	3400lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	171	340
0765043F-30	 spot 9°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	171	340
0765054F-30	 medium 25°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	171	340
0765005F-30	 wide flood 46°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	171	340
0765044F-30	 elliptic 9°x52°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	171	340
0765053F-30	 wall washer I _{max} =19°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	171	340


 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.

QUAD200

FLUSH TRIM - RECESSED DEEP BOX

Supplied with recessed installation box (1099035X).














STANDARD COLOUR

● 30



DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0765018A-840-30	 spot 9°	37W	4050lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	288	202
0765015A-840-30	 medium 25°	37W	3800lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	288	202
0765021A-840-30	 wide flood 47°	37W	3500lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	288	202
0765011A-840-30	 elliptic 9°x52°	37W	3700lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	288	202
0765048A-840-30	 wall washer I _{max} =19°	37W	3400lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	221	288	202
0765045F-30	 spot 9°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	288	202
0765056F-30	 medium 25°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	288	202
0765006F-30	 wide flood 46°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	288	202
0765046F-30	 elliptic 9°x52°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	288	202
0765055F-30	 wall washer I _{max} =19°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	221	288	202

The photo represents the family product range. You can see the correct image of each product (code) on the website.


LED driver included.

Recessed floor fittings

QUAD200

TRIM ABOVE THE GROUND - RECESSED L BOX


Supplied with recessed installation box (1099234X).













STANDARD COLOUR


 30

DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0765016A-840-30	 spot 9°	37W	4050lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	167	340
0765014A-840-30	 medium 25°	37W	3800lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	167	340
0765020A-840-30	 wide flood 47°	37W	3500lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	167	340
0765009A-840-30	 elliptic 9°x52°	37W	3700lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	167	340
0765049A-840-30	 wall washer I _{max} =19°	37W	3400lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	167	340
0765039F-30	 spot 9°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	167	340
0765058F-30	 medium 25°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	167	340
0765003F-30	 wide flood 46°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	167	340
0765040F-30	 elliptic 9°x52°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	167	340
0765057F-30	 wall washer I _{max} =19°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	167	340


 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.

QUAD200

TRIM ABOVE THE GROUND - RECESSED DEEP BOX

Supplied with recessed installation box (1099232X).














STANDARD COLOUR

● 30



DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0765017A-840-30	 spot 9°	37W	4050lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	284	202
0765013A-840-30	 medium 25°	37W	3800lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	284	202
0765019A-840-30	 wide flood 47°	37W	3500lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	284	202
0765010A-840-30	 elliptic 9°x52°	37W	3700lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	284	202
0765050A-840-30	 wall washer lmax=19°	37W	3400lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	230	284	202
0765041F-30	 spot 9°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	284	202
0765060F-30	 medium 25°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	284	202
0765004F-30	 wide flood 46°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	284	202
0765042F-30	 elliptic 9°x52°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	284	202
0765059F-30	 wall washer lmax=19°	40W			RGBW	⊕	DMX	220-240V 50/60Hz	230	284	202

The photo represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.

Recessed floor fittings


QUAD200

ACCESSORIES

It is possible to purchase the recessed box separately, whenever it is necessary to start the installation in advance. The item can be ordered later on and it will be supplied complete with recessed box (to be removed if purchased separately in advance).



Code	Kg	Code	Kg	Code	Kg	Code	Kg	Code	Kg	Code	Kg		
1099034X	1,60	1099035X	1,50	1099234X	1,60	1099232X	1,60	1099280X	0,70	1099407X	0,08	1099409X	0,03
L-shaped inground-recess box in galvanized steel for wire trim versions.		High inground-recess box in galvanized steel for wire trim versions.		L-shaped recess in galvanized steel.		High recess in galvanized steel.		Anti-slip opal glass. To order with the light fitting.		IP68 junction box - 4 ways - 4/5 poles.		IP68 linear joint - 2 ways - 3 poles.	

 These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".



Photorealistic rendering.