

T-RAIL



comfort



Arcluce Code **0782095C-940-34**

Ex Code

Code EAN **8054378021534**



Technical information

Light source:	LED, 4000K
Luminaire:	3.5W
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	CV 24V
Wiring:	REM-D
Optics:	extra wide flood 110°
Color:	colors.34
Weight:	0.5 kg
Size:	A: 35mm B: 80mm C: 250mm

CE

IP68

IK07

III

500

500

↓

Appliance

- Extruded aluminium body.
- AISI 316 stainless steel external screws.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 500Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Steel spring clips.
- Supplied with stainless steel recessed installation box.
- Supplied complete with power cable and plug.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- To complete the installation, the single connection kit or the kit for looping multiple devices is required.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

T-RAIL


comfort



Arcluce Code **0782095C-940-34**

Ex Code

Code EAN **8054378021534**



Specifications

The special structure with stainless steel counter housing and IP68 protection rating make T-RAIL a highly durable luminaire, which is suitable for functional lighting of urban and residential areas that are also exposed to the presence of water and moisture. Moreover, comfort optics made of tempered glass ensure a soft and pleasant lighting effect.

Extruded aluminium body. AISI 316 stainless steel external screws. Screen made of 8mm thermal-shock resistant tempered glass. 500Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum

Luminaire in insulation class III.

REMOTE DRIVER, NOT INCLUDED.

Recessed installation. Steel spring clips. Supplied with stainless steel recessed installation box.

Supplied complete with power cable and plug.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. T-RAIL

T-RAIL



comfort



Arcluce Code **0782096C-940-34**

Ex Code

Code EAN **8054378021589**



Technical information

Light source:	LED, 4000K
Luminaire:	7W
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	CV 24V
Wiring:	REM-D
Optics:	extra wide flood 110°
Color:	colors.34
Weight:	1 kg
Size:	A: 35mm B: 80mm C: 500mm

CE

IP68

IK07

III

500

500

↓

Appliance

- Extruded aluminium body.
- AISI 316 stainless steel external screws.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 500Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Steel spring clips.
- Supplied with stainless steel recessed installation box.
- Supplied complete with power cable and plug.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- To complete the installation, the single connection kit or the kit for looping multiple devices is required.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

T-RAIL


comfort



Arcluce Code **0782096C-940-34**

Ex Code

Code EAN **8054378021589**



Specifications

The special structure with stainless steel counter housing and IP68 protection rating make T-RAIL a highly durable luminaire, which is suitable for functional lighting of urban and residential areas that are also exposed to the presence of water and moisture. Moreover, comfort optics made of tempered glass ensure a soft and pleasant lighting effect.

Extruded aluminium body. AISI 316 stainless steel external screws. Screen made of 8mm thermal-shock resistant tempered glass. 500Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum

Luminaire in insulation class III.

REMOTE DRIVER, NOT INCLUDED.

Recessed installation. Steel spring clips. Supplied with stainless steel recessed installation box.

Supplied complete with power cable and plug.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. T-RAIL

T-RAIL



comfort



Arcluce Code **0782097C-940-34**

Ex Code

Code EAN **8054378021602**



Technical information

Light source:	LED, 4000K
Luminaire:	14W
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	CV 24V
Wiring:	REM-D
Optics:	extra wide flood 110°
Color:	colors.34
Weight:	1.95 kg
Size:	A: 35mm B: 80mm C: 1000mm

CE

IP68

IK07

III

500

500

↓

Appliance

- Extruded aluminium body.
- AISI 316 stainless steel external screws.
- Screen made of 8mm thermal-shock resistant tempered glass.
- 500Kg static load capacity.
- Can be walked over.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Steel spring clips.
- Supplied with stainless steel recessed installation box.
- Supplied complete with power cable and plug.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- To complete the installation, the single connection kit or the kit for looping multiple devices is required.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

T-RAIL


comfort



Arcluce Code **0782097C-940-34**

Ex Code

Code EAN **8054378021602**



Specifications

The special structure with stainless steel counter housing and IP68 protection rating make T-RAIL a highly durable luminaire, which is suitable for functional lighting of urban and residential areas that are also exposed to the presence of water and moisture. Moreover, comfort optics made of tempered glass ensure a soft and pleasant lighting effect.

Extruded aluminium body. AISI 316 stainless steel external screws. Screen made of 8mm thermal-shock resistant tempered glass. 500Kg static load capacity. Can be walked over. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum

Luminaire in insulation class III.

REMOTE DRIVER, NOT INCLUDED.

Recessed installation. Steel spring clips. Supplied with stainless steel recessed installation box.

Supplied complete with power cable and plug.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. T-RAIL