

Bollards

TULA



LUMINAIRE



- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Opal PMMA screen or 5mm thermal-shock resistant tempered safety glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-1.

INSTALLATION

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Different accessories to be ordered separately.

STANDARD PRODUCT		AVAILABLE OPTIONS
Wiring	PC= PHASE-CUT (P)	
CCT	4000K (-840)	3000K (-830)
Colour	 16	 21



Photorealistic rendering.

Bollards


TULA

PERFORMANCE






STANDARD COLOUR

● 16



DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0867005P-840-16	 radial	10W	525lm	80	4000K	⊕	PC	220-240V 50/60Hz	117	163	600
0867006P-840-16	 radial	10W	525lm	80	4000K	⊕	PC	220-240V 50/60Hz	117	163	900


 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

COMFORT






STANDARD COLOUR

● 16




DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0867001P-840-16	 radial	5W	300lm	80	4000K	⊕	PC	220-240V 50/60Hz	138	163	600
0867002P-840-16	 radial	5W	300lm	80	4000K	⊕	PC	220-240V 50/60Hz	138	163	900


 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

ACCESSORIES



Code	Kg
1099397X-16	0,40

Galvanized and painted steel base plate with galvanized steel stud bolts.



Code	Kg
1099259X	0,05

Junction box IP68 - 4 ways - 2/3 poles



Code	Kg
1099409X	0,03

IP68 linear joint - 2 ways - 3 poles.

LED driver included.



Photorealistic rendering.