



TULA Bollard

comfort

Arcluce Code **0867001P-840-16**

Ex Code

Code EAN **8054378334016**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	60lm/W
Luminaire:	5W , 300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	PC
Optics:	radial
Color:	Grey - 16
Weight:	2.2 kg
Size:	A: 138mm B: 163mm C: 600mm

CE

IP66

IK07



0,05m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Transparent microprismatic visible screen, internal screen in PMMA.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.


TULA Bollard

comfort

Arcluce Code **0867001P-840-16**

Ex Code

Code EAN **8054378334016**



Specifications

The elegant bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Transparent microprismatic visible screen, internal screen in PMMA. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 4000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 60lm/W
Luminaire in insulation class I.
DRIVER INCLUDED.
Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
Brand ARCLUCE mod. TULA Bollard



TULA Bollard

comfort

Arcluce Code **0867002P-840-16**

Ex Code

Code EAN **8054378334054**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	60lm/W
Luminaire:	5W , 300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	PC
Optics:	radial
Color:	Grey - 16
Weight:	2.7 kg
Size:	A: 138mm B: 163mm C: 900mm

CE

IP66

IK07



0,07m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Transparent microprismatic visible screen, internal screen in PMMA.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.




TULA Bollard

comfort

Arcluce Code **0867002P-840-16**

Ex Code

Code EAN **8054378334054**



Specifications

The elegant bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Transparent microprismatic visible screen, internal screen in PMMA. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 4000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 60lm/W
Luminaire in insulation class I.
DRIVER INCLUDED.
Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
Brand ARCLUCE mod. TULA Bollard



TULA Bollard

performance

Arcluce Code **0867005P-840-16**

Ex Code

Code EAN **8054378334092**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	53lm/W
Luminaire:	10W , 525lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	PC
Optics:	radial
Color:	Grey - 16
Weight:	2.21 kg
Size:	A: 117mm B: 163mm C: 600mm

CE

IP66

IK07



0,05m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Transparent microprismatic visible screen, internal screen in PMMA.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.


TULA Bollard

performance

Arcluce Code **0867005P-840-16**

Ex Code

Code EAN **8054378334092**



Specifications

The elegant bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Transparent microprismatic visible screen, internal screen in PMMA. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 4000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 53lm/W
Luminaire in insulation class I.
DRIVER INCLUDED.
Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
Brand ARCLUCE mod. TULA Bollard



TULA Bollard

performance

Arcluce Code **0867006P-840-16**

Ex Code

Code EAN **8054378334139**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	53lm/W
Luminaire:	10W , 525lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	PC
Optics:	radial
Color:	Grey - 16
Weight:	2.71 kg
Size:	A: 117mm B: 163mm C: 900mm

CE

IP66

IK07



0,07m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Transparent microprismatic visible screen, internal screen in PMMA.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.




TULA Bollard

performance

Arcluce Code **0867006P-840-16**

Ex Code

Code EAN **8054378334139**



Specifications

The elegant bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Transparent microprismatic visible screen, internal screen in PMMA. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 4000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 53lm/W
Luminaire in insulation class I.
DRIVER INCLUDED.
Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
Brand ARCLUCE mod. TULA Bollard