



VIZOR



VIZOR | direct/indirect light | white color



VIZOR

Lighting and furnishing with style.

VIZOR is the lighting solution that furnishes interiors with style. The recessed position of the light sources ensures high visual comfort and the independently controllable direct and indirect optics allow the creation of a customised lighting atmosphere that enhances spaces in residential, commercial or professional settings.



VIZOR

An elegant design with essential lines characterises this luminaire that guarantees high quality lighting.



LUMINAIRE

Extruded aluminium body; Die-cast aluminium end caps; Die-cast aluminium cable cup; Polyester powder paint resistant to UV rays; PMMA lenses for LEDs; High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80; It complies with standards EN 60598-1 and EN 60598-2-1.

INSTALLATION

Suspended installation; Galvanized steel base plate; Steel cable 1.5m for suspension; Cable cup with transparent power cable included.

Versions with Casambi and other modern control systems available, for more information see the "Light Control" section on page 468.

STANDARD PRODUCT

Color	Wiring	CCT
<input type="checkbox"/> 11 (-11)	ON/OFF (A), BLE (T)	3000K (-830)

AVAILABLE OPTIONS

<input checked="" type="checkbox"/> 12 (-12)	DALI (B)	4000K (-840)
--	----------	--------------

Variants



PENDANT LUMINAIRES




UGR<16

VIZOR

Code	Optic (indirect/direct)	Watt	Lumen	CRI	CCT	Class	Wiring	A	B mm	C
0246001T-11	ultra wide flood 100° wide flood 45°	58W	2400lm 2450lm	80	TW* 3000K	⊖	BLE	127	42	1200
0246000A-830-11	ultra wide flood 100° wide flood 45°	58W	2400lm 2350lm	80	3000K 3000K	⊕	ON/OFF	127	42	1200

*Tunable white



LIGHTING DATA



indirect

ultra wide flood 100°

wide flood 45°

direct

H (m)	Ø1 (m)	Ø2 (m)	LUX (max)
3,00	5,73	9,38	106
2,50	4,78	7,82	152
2,00	3,82	6,25	238
1,50	2,87	4,69	423
1,00	1,91	3,13	952
0,50	0,96	1,56	3807
0,50	0,41	0,42	16494
1,00	0,81	0,84	4124
1,50	1,22	1,27	1832
2,00	1,62	1,69	1030
2,50	2,03	2,11	660
3,00	2,44	2,53	458





indirect

ultra wide flood 100°

wide flood 45°

direct

H (m)	Ø1 (m)	Ø2 (m)	LUX (max)
3,00	5,73	9,38	106
2,50	4,78	7,82	152
2,00	3,82	6,25	238
1,50	2,87	4,69	423
1,00	1,91	3,13	952
0,50	0,96	1,56	3807
0,50	0,41	0,42	16494
1,00	0,81	0,84	4124
1,50	1,22	1,27	1832
2,00	1,62	1,69	1030
2,50	2,03	2,11	660
3,00	2,44	2,53	458



The product image in the grid represents the family. You can see the correct image of each product (code) on arcluce.it