

LUNA BL



Integrated

Reflector with integrated LED unit

Durable

Impact-resistant poly-carbonate casing (IK08)

HOUSING Polycarbonate, impact-resistant, IK08.

LAMP COVER Polycarbonate with integrated LED unit.

SEALS Ageing resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

ASSEMBLY Variable mounting distances with PRACHT-CLIP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.

FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 fluorescent light-exchange.

CONFIGURABILITY Possible in the LUNA PRO LINE. E.g.: light colors, control module, emergency lighting modules, cable inlets and a lot more.

Individual luminaire, color temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x20 W	120° wide	2500 lm	5211012	600 mm	1,2 kg
1x20 W	120° wide	2800 lm	5211004B	1200 mm	1,8 kg
1x39 W	120° wide	5400 lm	5211014B	1200 mm	1,8 kg
1x27 W	120° wide	3800 lm	5211005B	1500 mm	2,1 kg
1x47 W	120° wide	6500 lm	5211015B	1500 mm	2,1 kg

ACCESSORIES

Through-wiring	P/N
3x1,5mm ² Set LUNA BL 1,2m, consisting of rigid conductors, 2x5pin terminal block one-sided	5552132
3x1,5mm ² Set LUNA BL 1,5m, consisting of rigid conductors, 2x5pin terminal block one-sided	5552135
5x2,5mm ² Set LUNA BL 1,2m, consisting of rigid conductors, 2x5pin terminal block	5552152
5x2,5mm ² Set LUNA BL 1,5m, consisting of rigid conductors, 2x5pin terminal block	5552155

Protection class I according to EN 60598

Protection type IP65

AC 220-240 V 50/60 Hz




ALLROUNDER

EXTREMELY FAST ASSEMBLY
DIFFUSER LUMINAIRE
HIGH QUALITY
PRICE / PERFORMANCE **ENEC**
DUST-TIGHT HOMOGENEOUS LIGHT
1:1 REPLACEMENT

5
YEAR
WARRANTY


UP TO **100.000 h**
LIFETIME

IP65


FROM **-20°C**
TO **+35°C**

THE RIGHT OF ERROR AND LATER TECHNICAL DEVELOPMENTS IS RESERVED - 05 05 2023